



Base model shown with added options

All-around Efficiency

When it comes to transporting perishable cargo, the Kold King is the go-to for protecting products and maximizing operating efficiency. Available in a variety of sizes and configurations, the Kold King is the solution for the rigorous demands of multi-stop refrigerated delivery.

Features

- New foaming process for up to 25% greater thermal efficiency and fewer TRU hours
- ~200 lb weight reduction improves thermal and fuel efficiency while increasing payload
- Single and multi-temp options meet unique cargo requirements
- One Piece Header System eliminates corner caps, increasing front wall durability
- Smooth, seamless interior liner for a brighter, more durable food grade surface
- Overall design significantly reduces leak points and water intrusion for longer insulation life
- Solutions available for traditional, alternative fuel and electrified chassis




Specifications: Kold King


Width	Length	Height					
		79"	85"	91"	97"	103"	109"
96"	12'	•	•	•			
	14'	•	•	•			
	16'	•	•	•	•		
	18'		•	•	•		
	20'		•	•	•	•	
	22'		•	•	•	•	•
	24'		•	•	•	•	•
	26'			•	•	•	•
28'				•	•	•	
102"	18'		•	•	•		
	20'		•	•	•	•	
	22'		•	•	•	•	•
	24'		•	•	•	•	•
	26'			•	•	•	•
	28'				•	•	•

Available sizes limited by chassis type

Interior Lights	<ul style="list-style-type: none"> • LED dome light with rear switch - hot wired
Exterior Lights	<ul style="list-style-type: none"> • LED clearance lights • Existing chassis taillights
Bumper	<ul style="list-style-type: none"> • Pooched ICC
Warranty	<ul style="list-style-type: none"> • 1-year white surface and leaks • 3-year/36,000-mile limited bulkhead-to-bumper warranty • 5-year limited structural warranty (roof, wall and floor structure) • See our warranty policy for details
Options	Contact your representative or visit supremetruckbody.com for more options to meet your unique requirements.



Anti-skid Intervrted-T Floor



Anti-skid Box-type Reefer

Chassis Type	<ul style="list-style-type: none"> • Cab
Truck Body Type	<ul style="list-style-type: none"> • Insulated
Available Sidewalls	<ul style="list-style-type: none"> • .040" smooth aluminum pre-painted white panels
Lining	<ul style="list-style-type: none"> • Seamless, anti- microbial composite walls, roof and front wall.
Insulation	<ul style="list-style-type: none"> • 3" side walls and roof, 4" front wall and floor
Front	<ul style="list-style-type: none"> • FiberPanel® (FRP) white front wall • One Piece Header System • Extruded-aluminum radius vertical front corners
Rear Frame	<ul style="list-style-type: none"> • Painted galvanized steel • 14 ga. header • 12 ga. corner posts • 10 ga. one-piece V-groove threshold • Internal gussets
Rear Door	<ul style="list-style-type: none"> • High-temp insulated • Maximum Security (MS) lock
Floor	<ul style="list-style-type: none"> • Smooth box type extruded aluminum floor
Subframe	<ul style="list-style-type: none"> • 3" I-beam cross members on 12" C/L • 4" I-beam longsills • Full-perimeter steel reinforcing aluminum rub rail • Pre-coated understructure
Roof	<ul style="list-style-type: none"> • One-piece .032" aluminum skin • Galvanized-steel anti-snag roof bows on 24" C/L



Folding Reefer Steps



Reefer Service Platform

Call 800-642-4889 Online supremetruckbody.com

Base specifications are accurate at the time of publication, and are subject to change without notice. Custom options are available; please consult your representative for additional information.
©2020 Wabash National L.P. All rights reserved.

SUP 0002 11.20

SUPREME
BY WABASH